US Serial No. 10/561749 Page 2 of 10 RECEIVED CENTRAL FAX CENTER MAY 1 8 2010

In the Claims:

- 1.(currently amended) A device <u>adapted to be installed and used useful in conjunction</u> with a toilet bowl or other sanitary appliance which device provides for the delivery of a treatment composition, which contains one or more active agents such as a coloring agent, cleaning agent, disinfecting agent, and/or an antilime scale agent or a mixture of two or more of these agents, while simultaneously providing a <u>continuous</u> fragrancing effect to the ambient environment of the sanitary appliance as well, wherein the device includes
 - (a) a first dispenser for containing a treatment composition, which first dispenser permits for passage of water contained within the sanitary appliance into and out of contact with the <u>first dispenser containing</u> said treatment composition and with said treatment composition;
 - (b) a second dispenser for containing a fragrancing composition, which, during the use of the device, the fragrancing composition desirably does not contact water in the sanitary appliance, and
 - (c) a hanger <u>intermediate to and</u> connecting the first dispenser to the second dispenser <u>wherein said first dispenser is separate from the said second dispenser</u>, which hanger is adapted for removably hanging the device upon a portion of a sanitary appliance.
- 2. (original) A device according to claim 1 wherein the first dispenser comprises a sidewall having at least one perforation passing through said sidewall.
- (original) A device according to claim 1 wherein the second dispenser comprises a cavity containing a fragrance composition.
- 4. (previously presented) A device according to claim 1 wherein the hanger is flexible.

US Serial No. 10/561749 Page 3 of 10

- 5. (previously presented) A device according to claim 1 wherein the hanger includes a bridge section having two downwardly depending legs.
- 6. (previously presented) A device according to claim 1 wherein the hanger includes a bridge section having two downwardly depending legs having different lengths.
- 7. (previously presented) A device according to claim 1 wherein the treatment composition is in the form of a solid block.
- 8. (previously presented) A device according to claim 1 wherein the treatment composition is in the form of a gel.

9.(canceled)

10.(currently amended) A process for delivering a treatment composition to the interior of a sanitary appliance, particularly a toilet bowl, which process comprises the process steps of: eontemplates

providing a device according as described with reference to claim 1, and installing the device within or upon at least a portion of a sanitary appliance such that, whereby the said treatment composition of the first dispenser contacts water contained within the sanitary appliance, while the second dispenser continuously provides simultaneously providing a fragrancing effect to ambient environment of the sanitary appliance.

11.(new) A device adapted to be installed upon a cistern of a toilet bowl or other sanitary appliance having a cistern which device provides for the delivery of a treatment composition to the interior of the cistern, which contains one or more active agents such as a coloring agent, cleaning agent, disinfecting agent, and/or

US Serial No. 10/561749 Page 4 of 10

an anti-lime scale agent or a mixture of two or more of these agents to water contained within the cistern, while simultaneously providing a continuous fragrancing effect to the ambient environment of the sanitary appliance exterior of the cistern, wherein the device includes

- (a) a first dispenser for containing a treatment composition, which first dispenser permits for passage of water contained within the cistern of the sanitary appliance into contact with the said first dispenser containing said treatment composition and with said treatment composition contained within the cistern;
- (b) a second dispenser for containing a fragrancing composition, which, during the use of the device, the fragrancing composition desirably does not contact water in the sanitary appliance contained within the cistern, and
- (c) a hanger connecting the first dispenser to the second dispenser wherein said first dispenser is separate from the said second dispenser, which hanger is adapted for removably hanging the device upon a portion of the cistern of the sanitary appliance.
- 12. (new) A device according to claim 11 wherein the first dispenser comprises a sidewall having at least one perforation passing through said sidewall.
- 13. (new) A device according to claim 11 wherein the second dispenser comprises a cavity containing a fragrance composition.
- 14. (new) A device according to claim 11 wherein the hanger includes a bridge section having two downwardly depending legs.
- 15. (new) A device according to claim 11 wherein the hanger includes a bridge section having two downwardly depending legs having different lengths.